

HM 098

Shurtape®
TRUE TO YOUR WORK™

GENERAL PURPOSE GRADE HOT MELT PACKAGING TAPE

TYPICAL APPLICATIONS

- For manual or automated industrial carton sealing of lightweight cartons with minimal exposure to handling, shipping and load stress

PRODUCT FEATURES

- Instant, permanent bond to a wide range of substrates and surfaces
- Special release coating for consistent, low force unwind off the roll
- Performs reliably to the core for efficient tape consumption
- High-tack adhesive for a long-lasting, secure seal

CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: 38 micron biaxially oriented polypropylene cast film

Adhesive: Synthetic rubber/resin hot melt

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

150 m 914 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

GB / 7125 - 1999; GB / 4852 - 2002; GB / 2792 - 1998;

GB / 7753 - 1987

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

STANDARD

METRIC

Thickness	1.5 mils	0.038 mm
Tensile Strength	21 lbs/in width	36.8 N/10 mm
Elongation	180%	180%
Adhesion to Stainless Steel	46.3 oz/in width	4.71 N/10 mm
Adhesion to Backing	18 oz/in width	1.97 N/10 mm
Application Temperature Range	14 F to 140 F	-10 C to 60 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

