

## Flock-Lined Neoprene Over Rubber Gloves

### DESCRIPTION

These 26-mil unsupported gloves feature blue neoprene over a yellow rubber shell. The flock-lined interior absorbs moisture for comfortable extended use. The raised diamond pattern is excellent for wet grip and they are 13 inches in length.



### INDUSTRY

Chemical Processing    Petrochemical  
 Food Processing        Maintenance  
 Janitorial

### FEATURES

- EN 374 Levels: AKLMNOPST
- EN 388 Levels: 2110X
- Raised diamond pattern is excellent for wet grip
- Flock-lined interior absorbs moisture off the skin for more comfortable extended wear
- Neoprene over rubber is chemical, oil and solvent resistant
- Diamond pattern grip is effective in wet or oily conditions

ITEM 244

SIZES 7(S)-10(XL)



### SPECIFICATIONS

SHELL	COLOR	FINISH	LINING	LINING COLOR	
Neoprene over Rubber	Blue/Yellow	Raised Diamond	Flock Lined	White	
LENGTH	THICKNESS	CUFF	EN 388 LEVELS	EN 374 LEVELS	FDA FOOD CONTACT
13 in	26 mil	Straight	2110X	AKLMNOPST	Compliant

### PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)
PAIR UPC	1	N/A	N/A	N/A	N/A
INNER PACK UPC	12/PACK	816679014633	816679014640	816679014657	816679014664
CASE UPC	6 PK/CASE	810292023348	810292023355	810292023362	810292023379
CASE WEIGHT (IN POUNDS)		28.2	33	36	36

### PERMEATION DATA

EN ISO 374-01: 2016	CHEMICAL	PL
A	Methanol	2
K	Sodium Hydroxide 40%	6
L	Sulfuric Acid 96%	3
M	Nitric Acid 65%	5
N	Acetic Acid 99%	2
O	Ammonium Hydroxide 25%	1
P	Hydrogen Peroxide 30%	6
S	Hydrofluoric Acid 40%	6
T	Formaldehyde 37%	6

PERMEATION DATA WAS MEASURED IN TWO WAYS:  
 1. FOR SOLVENTS – GAS CHROMATOGRAPHY  
 2. FOR ACID AND BASES – BY CONDUCTIVITY MEASUREMENTS

\* PL = Performance level